



## TOP MOUNTINGS PEDESTRIAN SIGNALS AND MOUNTINGS

TP-I-T



TP-I

30



TP-2-T

PEDESTRIAN SIGNAL FACE SYMBOL TYPE





#### INTERNALLY ILLUMINATED SIGN METER ON TYPE

### NOTES

- I. Mounting shall be oriented to provide maximum horizontal clearance to adjacent roadway.
- 2. Pedestrian signals shall be positioned on the side of standard nearest crosswalk controlled.
- 3. Bracket arms shall be long enough to permit proper alignment of signals.
- 4. See Standard Plan ES-4D for attachment fitting details.

### **ABBREVIATIONS**

TP - Top mounted pedestrian signal

SP - Side mounted pedestrian signal

T - Terminal compartment

I, 2 - Number of signal faces

STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION

# SIGNAL, LIGHTING AND **ELECTRICAL SYSTEMS** SIGNAL HEADS AND MOUNTINGS

These "Standard Plans for Construction of Local Streets and Roads" contain units in two systems of measurements international System of Units (SI or "metric") and United States
Standard Measures shown in the parentheses (). The measurements expressed in the
two systems are not necessarily equal or interchangeable. See the "Foreword" at the
beginning of this publication.

NO SCALE

ES-4B